

Data Sheet

Itemnumber..... 3222001199



| | | | | | | | | |
|----------|----------|----------|----------|---------|---------|-----------|----------|----------|
| A = 318 | AC = 397 | BB = 369 | DB = M20 | EG = 50 | GD = 10 | HB = 263 | L = 779 | TL = 192 |
| AA = 70 | AD = 313 | C = 133 | E = 110 | F = 16 | H = 200 | HD = 513 | LB = 669 | |
| AB = 388 | B = 305 | D = 55 | EB = 90 | G = 49 | HA = 25 | K = 18,50 | TB = 260 | |

Version

Type..... HMC2 200L2-2
Design..... Induction motor
Standard series..... IEC 60034
Phase / Voltage range..... 3~ / Low

Electrical design

Efficiency..... IE2
Pole..... 2
Power at 50 Hz (kW)..... 37,0
Hz..... 60 (60 Hz output)
Voltage..... 690V
Winding voltage..... 690V 60 Hz
Power output (kW)..... 43,0
Duty..... S1
Insulation class..... F
Temperature rise..... B

Mechanical design

Frame size..... 200
Mounting..... B3
Rain cap..... No
Protection class..... IP55
Cooling method..... IC411/TEFC
External grounding..... Yes
Drain hole..... Yes
Frame material..... Cast Iron
Material approval..... None
Shaft..... IEC Standard
Key..... Closed key
Balancing..... Half key balancing
Vibration class..... Grade-A
Weight (kg)..... 265

Environment condition

Ambient temp. min. (°C)..... -20
Ambient temp. max. (°C)..... 45
Altitude (mtr up to)..... 1000

Bearing

DE Bearing..... 6312-ZZ/C3
NDE Bearing..... 6312-ZZ/C3
Fixed bearing..... DE

Terminal box

Tbox position..... Top
Cable entry direction..... Right (from DE)
Cable entry
Main..... 2 x M50x1,5
Ø32-38mm metal
Accessory..... 2 x M20x1,5
Metal blindcaps
Terminal board thread..... 6-M8

Test values

Rotor inertia (kgm²)..... 0,16
Noise level (dB(A))..... 75
No load current (A)..... 9,95
Winding resist. (ohm)..... 0,22
Starting time (sec.)..... 0,14
Temp. rise winding (K)..... 77
Temp. rise surface (K)..... 65

Motor protection

Thermal protection main..... PTC 3x 155 dgr
Thermal protection second..... None
Space heater..... 1x 230V 60W
Temperature detector..... No
SPM..... No
IR wire..... Yes
Tropical insulation..... Yes

Explosion protection

According to..... None
Type of protection..... None

General

Direction of rotation..... CW
Painting..... RAL 9005
Nameplate..... Multivoltage + VFD
Special packing..... No
Special requirements..... No

| | | | |
|---------------------------|------------------|------------------|------------------|
| Rated power (kW) | 37,0 | 44,5 | 43,0 |
| Frequency (Hz) | 50 | 60 | 60 |
| Voltage (V) | 575 | 690 | 690 |
| Connection | D | D | D |
| Full load current (A) | 44,5 | 45,5 | 44,0 |
| Speed (rpm) | 2950 | 3540 | 3540 |
| Power factor cos(phi) | 0,91 | 0,91 | 0,91 |
| Efficiency, 100/75/50 (%) | 92,5/ 92,5 /91,4 | 92,5/ 92,5 /91,4 | 92,5/ 92,5 /91,4 |
| Ist/In | 8,50 | 8,50 | 8,75 |
| Full load torque (Nm) | 120 | 120 | 116 |
| Tst/Tn | 3,10 | 3,10 | 3,15 |
| Tmax/Tn | 3,90 | 3,90 | 4,00 |
| Duty | S1 | S1 | S1 |
| Ambient temp. (°C) | 40 | 40 | 45 |