

Data Sheet

Itemnumber.....: 5563150102



A = 508	AC = 618	BB = 570	DB = M20	EG = 56	GD = 14	HB = 430	L = 1223	TL = 299
AA = 120	AD = 547	C = 216	E = 170	F = 22	H = 315	HD = 862	LB = 1053	
AB = 628	B = 406	D = 80	EB = 160	G = 71	HA = 45	K = 28	TB = 420	

Version

Type.....: HMC3 315S-6
Design.....: Induction motor
Standard series.....: IEC 60034
Phase / Voltage range.....: 3~ / Low

Electrical design

Efficiency.....: IE3
Pole.....: 6
Power at 50 Hz (kW).....: 75,0
Hz.....: 50
Voltage.....: 400VD/690VY
Winding voltage.....: 400VD/690VY 50 Hz
Power output (kW).....: 75,0
Duty.....: S1
Insulation class.....: F
Temperature rise.....: B

Mechanical design

Frame size.....: 315
Mounting.....: B3
Rain cap.....: No
Protection class.....: IP55
Cooling method.....: IC411/TEFC
External grounding.....: Yes
Drain hole.....: Yes
Frame material.....: Cast Iron
Material approval.....: None
Shaft.....: IEC standard
Key.....: Closed key
Balancing.....: Half key balancing
Vibration class.....: Grade-A
Weight (kg).....: 864

Environment condition

Ambient temp. min. (°C).....: -20
Ambient temp. max. (°C).....: 40
Altitude (mtr up to).....: 1000

Bearing

DE Bearing.....: 6319/C3
NDE Bearing.....: 6319/C3
Fixed bearing.....: DE

Terminal box

Tbox position.....: Top
Cable entry direction.....: Right (from DE)
Cable entry
Main.....: 2 x M63x1,5
Plastic blindcaps
Accessory.....: 2 x M20x1,5
Plastic blindcaps
Terminal board thread.....: 6-M16

Motor protection

Thermal protection main.....: PTC 3x 155 dgr
Thermal protection second.....: None
Space heater.....: None
Temperature detector.....: No
SPM.....: No
IR wire.....: No
Tropical insulation.....: No

Explosion protection

According to.....: None
Type of protection.....: None

General

Direction of rotation.....: CW
Painting.....: RAL 9005
Nameplate.....: Multivoltage
Special packing.....: No
Special requirements.....: No

Test values

Rotor inertia (kgm²).....: 4,24
Noise level (dB(A)).....: 75
No load current (A).....: 36,0
Winding resist. (ohm).....: 0,055
Starting time (sec.).....: 0,37
Temp. rise winding (K).....: 66
Temp. rise surface (K).....: 52

Rated power (kW)	75,0	73,0	90,0	87,5
Frequency (Hz)	50	50	60	60
Voltage (V)	400 Y 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	132 76,0	136 78,5	132 76,0	136
Speed (rpm)	990	990	1180	1180
Power factor cos(phi)	0,87	0,88	0,87	0,88
Efficiency, 100/75/50 (%)	94,6/ 94,9 /94,4	94,6/ 94,9 /94,4	94,6/ 94,9 /94,4	94,2/ 94,5 /94,0
Ist/In	5,80	5,10	5,80	5,35
Full load torque (Nm)	725	705	725	705
Tst/Tn	2,00	1,86	2,00	1,72
Tmax/Tn	2,30	2,14	2,30	2,00
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45