


Data Sheet

Itemnumber..... 5563551400



A = 610	AC = 699	BB = 750	DB = M24	EG = 56	GD = 14	HB = 489	L = 1537	M = 740	S = 8-Ø24	TL = 330
AA = 116	AD = 664	C = 254	E = 170	F = 25	H = 355	HD = 1019	LA = 25	N = 680	T = 6	
AB = 726	B = 560	D = 95	EB = 160	G = 86	HA = 52	K = 28	LB = 1367	P = 800	TB = 460	

Version

Type..... HMC3 355M2-6
Design..... Induction motor
Standard series..... IEC 60034
Phase / Voltage range..... 3~ / Low

Electrical design

Efficiency..... IE3
Pole..... 6
Power at 50 Hz (kW)..... 200
Hz..... 50
Voltage..... 400VD/690VY
Winding voltage..... 400VD/690VY 50 Hz
Power output (kW)..... 200
Duty..... S1
Insulation class..... F
Temperature rise..... B

Mechanical design

Frame size..... 355
Mounting..... B35
Rain cap..... No
Protection class..... IP55
Cooling method..... IC411/TEFC
External grounding..... Yes
Drain hole..... Yes
Frame material..... Cast Iron
Material approval..... None
Shaft..... IEC standard
Key..... Closed key
Balancing..... Half key balancing
Vibration class..... Grade-A
Weight (kg)..... 1.790

Environment condition

Ambient temp. min. (°C)..... -20
Ambient temp. max. (°C)..... 40
Altitude (mtr up to)..... 1000

Bearing

DE Bearing..... 6322/C3
NDE Bearing..... 6322/C3
Fixed bearing..... DE

Terminal box

Tbox position..... Top
Cable entry direction..... Right (from DE)
Cable entry
Main..... 2 x M72x2,0
Metal blindcaps
Accessory..... 2 x M20x1,5
Metal blindcaps
Terminal board thread..... 6-M16

Motor protection

Thermal protection main..... PTC 3x 155 dgr
Thermal protection second..... None
Space heater..... None
Temperature detector..... No
SPM..... No
IR wire..... No
Tropical insulation..... No

Explosion protection

According to..... None
Type of protection..... None

General

Direction of rotation..... CW
Painting..... RAL 9005
Nameplate..... Multivoltage
Special packing..... No
Special requirements..... No

Test values

Rotor inertia (kgm²)..... 12,3
Noise level (dB(A))..... 82
No load current (A)..... 87,5
Winding resist. (ohm)..... 0,019
Starting time (sec.)..... 0,41
Temp. rise winding (K)..... 74
Temp. rise surface (K)..... 58

Rated power (kW)	200	194	240	232
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	340 196	350 202	340 196	350
Speed (rpm)	990	990	1190	1190
Power factor cos(phi)	0,89	0,90	0,89	0,90
Efficiency, 100/75/50 (%)	95,8/ 96,0 /94,8	95,8/ 96,0 /94,8	95,8/ 96,0 /94,8	95,5/ 95,7 /94,5
Ist/In	6,05	5,30	6,05	5,55
Full load torque (Nm)	1.940	1.880	1.940	1.880
Tst/Tn	2,00	1,86	2,00	1,74
Tmax/Tn	2,20	2,04	2,20	1,90
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45