


# Data Sheet

Itemnumber..... 6042250400



A = 356	AC = 445	BB = 361	DB = M20	EG = 58	GD = 11	HB = 195	L = 821	M = 400	S = 8-Ø18,5	TL = 250
AA = 79	AD = 319	C = 149	E = 140	F = 18	H = 225	HD = 544	LA = 20	N = 350	T = 5	
AB = 426	B = 286	D = 60	EB = 125	G = 53	HA = 28	K = 18,50	LB = 681	P = 450	TB = 200	

## Version

Type..... HMC4 225S-4  
Design..... Induction motor  
Standard series..... IEC 60034  
Phase / Voltage range..... 3~ / Low

## Electrical design

Efficiency..... IE4  
Pole..... 4  
Power at 50 Hz (kW)..... 37,0  
Hz..... 50  
Voltage..... 400VD/690VY  
Winding voltage..... 400VD/690VY 50 Hz  
Power output (kW)..... 37,0  
Duty..... S1  
Insulation class..... F  
Temperature rise..... B

## Mechanical design

Frame size..... 225  
Mounting..... B35  
Rain cap..... No  
Protection class..... IP55  
Cooling method..... IC411/TEFC  
External grounding..... Yes  
Drain hole..... Yes  
Frame material..... Cast Iron  
Material approval..... None  
Shaft..... IEC standard  
Key..... Closed key  
Balancing..... Half key balancing  
Vibration class..... Grade-A  
Weight (kg)..... 344

## Environment condition

Ambient temp. min. (°C)..... -20  
Ambient temp. max. (°C)..... 40  
Altitude (mtr up to)..... 1000

## Bearing

DE Bearing..... 6213/C3  
NDE Bearing..... 6212/C3  
Fixed bearing..... DE

## Terminal box

Tbox position..... Top  
Cable entry direction..... Right (from DE)  
Cable entry  
Main..... 2 x M50x1,5  
Plastic blindcaps  
Accessory..... 2 x M20x1,5  
Plastic blindcaps  
Terminal board thread..... M8

## Test values

Rotor inertia (kgm²)..... 0,61  
Noise level (dB(A))..... 70  
Starting time (sec.)..... 0,19

## Motor protection

Thermal protection main..... PTC 3x 155 dgr  
Thermal protection second.. None  
Space heater..... None None  
Temperature detector..... No  
SPM..... No  
IR wire..... No  
Tropical insulation..... No

## Explosion protection

According to..... None  
Type of protection..... None

## General

Direction of rotation..... CW  
Painting..... RAL 9005  
Nameplate..... Multivoltage  
Special packing..... No  
Special requirements..... No

Rated power (kW)	37,0	36,0	44,5	43,0
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	64,5 37,0	66,5 38,5	64,5 37,0	66,5
Speed (rpm)	1480	1480	1780	1780
Power factor cos(phi)	0,87	0,88	0,87	0,88
Efficiency, 100/75/50 (%)	95,2/95,3/94,9	95,2/95,3/94,9	95,2/95,3/94,9	94,9/95,0/94,5
Ist/In	9,00	7,90	9,00	8,30
Full load torque (Nm)	238	232	238	232
Tst/Tn	2,40	2,24	2,40	2,08
Tmax/Tn	2,80	2,60	2,80	2,42
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45