


Data Sheet

Itemnumber.....: 6061800400



A = 279	AC = 355	BB = 342	DB = M16	EG = 42	GD = 9	HB = 227	L = 723	M = 300	S = 4-Ø18,5	TL = 181
AA = 70	AD = 256	C = 121	E = 110	F = 14	H = 180	HD = 436	LA = 15	N = 250	T = 5	
AB = 347	B = 279	D = 48	EB = 100	G = 42,50	HA = 25	K = 14,50	LB = 613	P = 350	TB = 181	

Version

Type.....: HMA4 180L-6
Design.....: Induction motor
Standard series.....: IEC 60034
Phase / Voltage range.....: 3~ / Low

Electrical design

Efficiency.....: IE4
Pole.....: 6
Power at 50 Hz (kW).....: 15,0
Hz.....: 50
Voltage.....: 400VD/690VY
Winding voltage.....: 400VD/690VY 50 Hz
Power output (kW).....: 15,0
Duty.....: S1
Insulation class.....: F
Temperature rise.....: B

Mechanical design

Frame size.....: 180
Mounting.....: B35
Rain cap.....: No
Protection class.....: IP55
Cooling method.....: IC411/TEFC
External grounding.....: Yes
Drain hole.....: Yes
Frame material.....: Aluminium
Material approval.....: None
Shaft.....: IEC standard
Key.....: Closed key
Balancing.....: Half key balancing
Vibration class.....: Grade-A
Weight (kg).....: 170

Environment condition

Ambient temp. min. (°C).....: -20
Ambient temp. max. (°C).....: 40
Altitude (mtr up to).....: 1000

Bearing

DE Bearing.....: 6311/C3
NDE Bearing.....: 6211/C3
Fixed bearing.....: DE

Terminal box

Tbox position.....: Top
Cable entry direction.....: Right (from DE)
Cable entry
Main.....: 2 x M40x1,5
Plastic blindcaps
Accessory.....: 2 x M20x1,5
Plastic blindcaps
Terminal board thread.....: M6

Test values

Rotor inertia (kgm²).....: 0,38
Noise level (dB(A)).....: 59
Starting time (sec.).....: 0,10

Motor protection

Thermal protection main.....: PTC 3x 155 dgr
Thermal protection second..: None
Space heater.....: None None
Temperature detector.....: No
SPM.....: No
IR wire.....: No
Tropical insulation.....: No

Explosion protection

According to.....: None
Type of protection.....: None

General

Direction of rotation.....: CW
Painting.....: RAL 9005
Nameplate.....: Multivoltage
Special packing.....: No
Special requirements.....: No

Rated power (kW)	15,0	14,6	18,0	17,4
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	30,0 17,4	31,0 17,8	30,0 17,4	31,0
Speed (rpm)	980	980	1180	1180
Power factor cos(phi)	0,78	0,79	0,78	0,80
Efficiency, 100/75/50 (%)	92,9/ 92,7 /90,7	92,9/ 92,7 /90,7	92,9/ 92,7 /90,7	92,4/ 92,2 /90,0
Ist/In	8,50	7,50	8,50	7,80
Full load torque (Nm)	146	142	146	142
Tst/Tn	3,00	2,80	3,00	2,60
Tmax/Tn	3,40	3,15	3,40	2,95
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45