

Disclaimer:
Parker PMDE has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact their local Parker dealer for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's standard conditions of sale.

F11-014-RB-SV-S-000-0000-0T

F11-014




Pump & Motor Division Europe




F11 Pump



F12 Pump





F11-014-RB-SV-S-000-0000-0T	
DISPLACEMENT	014 = 14.3 cc / 0.87 cu.in.
FUNCTION	R = Pump, Clockwise Rotation
MAIN PORTS	B = BSP Threads
MOUNTING FLANGE	S = SAE 2 Flange
SHAFT SEAL	V = FPM, High Pressure, High Temperature
SHAFT	S = SAE Spline, Standard
VERSION NUMBER	000 = Standard
OPTION1	0000 = Standard
OPTION2	0T = Standard, painted black
WEIGHT	8.3 - [kg]

Disclaimer:
Parker PMDE has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact their local Parker dealer for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's standard conditions of sale.

F11-014-RB-SV-S-000-0000-0T

F11-014



Pump & Motor Division Europe



F11 Pump



F12 Pump