

Disclaimer:
Parker PMDE has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact their local Parker dealer for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's standard conditions of sale.

F12-162-RM-SV-T-000-0000-P0

F12-162




Pump & Motor Division Europe



F11 Pump



F12 Pump



F12-162-RM-SV-T-000-0000-P0	
DISPLACEMENT	162 = 163.1 cc / 9.88 cu.in.
FUNCTION	R = Pump, Clockwise Rotation
MAIN PORTS	M = SAE 6000 psi, Side
MOUNTING FLANGE	S = SAE 4 Flange
SHAFT SEAL	V = FPM, High Pressure, High Temperature
SHAFT	T= SAE Key, Standard
VERSION NUMBER	000 = Standard
OPTION1	0000 = Standard
OPTION2	P0 = Standard, prepared for speed sensor
WEIGHT	40.0 - [kg]

Disclaimer:
Parker PMDE has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact their local Parker dealer for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's standard conditions of sale.

F12-162-RM-SV-T-000-0000-P0

F12-162



Pump & Motor Division Europe

